

# CDMA Easy Programming

## THIS IS THE PREFERRED PROGRAMMING METHOD

Before you start,

- Write down your client's cellular phone number here (     )  -       ,
- your Carrier Analog System ID\* (a one to five digit number) here      ,
- and your Carrier Digital System ID\* here      .

\*Contact your Cellular Service Provider to confirm your Carrier System ID number.

	TO	ENTER	PHONE DISPLAYS
1	Enter <b>NAM 1*</b> Programming Mode	PRESS <b>(7)</b> , <b>(4)</b> , <b>(6)</b> , <b>(6)</b> , <b>(3)</b> , <b>(#)</b> , <b>(1)</b> , <b>(FCN)</b> , <b>(FCN)</b>	Enter MIN
2	Enter your phone number	Use the keypad to enter all ten digits of your phone number and press <b>(STO)</b> .	Sample Number: 312-555-1212
3	Enter AMPS System ID (Analog)	Enter _ _ _ _ _ . Press <b>(STO)</b> .	Sample Number: 11111
4	Enter Digital System ID	Enter _ _ _ _ _ . Press <b>(STO)</b> .	Sample Number: 11111

*Don't worry!* If you make a mistake, press **(CLR)** to erase the last digit or press and hold **(CLR)** to erase the entire entry. Re-enter the correct number, then press **(STO)** and you're finished!

## PROGRAMMING NAM 2\*

Follow steps 1-4 for programming NAM 2 also, EXCEPT in the step one sequence press **(2)** for line NAM 2; i.e., enter P-H-O-N-E **(#)**, then **(2)**, **(FCN)**, **(FCN)**, and follow steps 2-4 again.

\*CDMA technology allows for two separate phone numbers to be programmed into the phone.

