A subsidiary of BMW AG US Press Information



For Release: May 1, 2007

Contact: Thomas Plucinsky Product and Technology Communications Manager 201-307-3783 / <u>thomas.plucinsky@bmwna.com</u>

> William Scully BMW Product Communications Specialist 201-307-3790 / <u>william.scully@bmwna.com</u>

2008 BMW 5 SERIES Technical Specifications

	General	528i Sedan	528xi Sedan	535i Sedan	535xi Sedan	535xi Sports	550i Sedan
Company						Wagon	
BMW of North America, LLC BMW Group Company	Curb weight, lb.:						
	Manual transmission	3505	3770	TBD	TBD	TBD	3946
Mailing address PO Box 1227 Westwood, NJ	Automatic transmission	3571	3814	3704	3946	4145	3968
07675-1227	Weight distribution, front/rear, %:						
Office address 300 Chestnut Ridge Road	Manual transmission	49.7/50.3	51.8/48.2	TBD	TBD	TBD	51.4/48.6
Woodcliff Lake, NJ 07677-7731	Automatic transmission	50.3/49.7	52.0/48.0	51.8/48.2	53.4/46.6	49.2/50.8	51.7/48.3
Telephone	Wheelbase, in.	113.7 ¹				113.6	

Telephone (201) 307-3606

Fax (201) 307-3607

Internet

bmwusa.com

^m ¹ – Specification applies to all Sedan models.



Body	528i Sedan	528xi Sedan	535i Sedan	535xi Sedan	535xi Sports Wagon	550i Sedan
Track, front/rear, in. (w/std. wheel	s)	61.3/62.2 ¹				61.3/62.2
Length, in.	191.1 ¹				191.2	
Width, in.	72.7 ²					
Height, in.	57.8	58.3	57.8	58.3	58.7	57.8
Туре	4-door sedan	1			5-door wagor	า
Aerodynamic drag coefficient	0.29	0.28	0.29	0.31	0.33	0.29
EPA size classification	Midsize ¹				Midsize sta. wagon	
Accommodations	528i Sedan	528xi Sedan	535i Sedan	535xi Sedan	535xi Sports Wagon	550i Sedan
Seating capacity, persons	5 ²					
Shoulder room, front/rear, in.	57.3/57.2 ²					
Head room, front/rear, in.	39.1/38.1 ¹				39.1/39.1	
Leg room, front/rear, in.	41.5/36.0 ²					
EPA passcompartment vol., cu f	t. 99.1 ¹				96.5	
EPA cargo volume, cu ft.	14.0 ³				17.6/33.6/58.	3 4

 $^{^2}$ – Specification applies to all models.

³ – Can be expanded via available folding rear seats.

⁴ – Rear seats upright, loaded to top of seats/rear seats upright, loaded to ceiling/rear seats folded, loaded to ceiling.

Engine & electrical	528i Sedan	528xi Sedan	535i Sedan	535xi Sedan	535xi Sports Wagon	550i Sedan
Engine type	6-cylinder, magnesium/ aluminum composite construction, Valvetronic variable intake-valve lift & Double VANOS ⁵ steplessly variable intake- & exhaust-valve timing ⁶		DOHC inline 24-valve 6- cylinder, aluminum construction with cast-iron cylinder liners, direct fuel injection with piezo injectors, twin turbochargers, Double VANOS ⁵ steplessly variable intake- & exhaust valve timing ⁷			DOHC (4 cam) 32-valve V-8, all aluminum construc- tion, Valvetronic variable intake- valve lift & Double VANOS ⁵ steplessly variable intake- & exhaust valve timing
Bore x stroke, mm/in.	85.0 x 88.0/3.35 x 3.46 ⁶		84.0 x 89.6/3.31 x 3.53 ⁷			93.0 x 88.3/ 3.66 x 3.48
Displacement, cc/cu in.	Displacement, cc/cu in. 2996/183 ⁶		2979/182 ⁷			4799/293
Compression ratio	10.7 ⁶		10.2:1 ⁷			10.5:1
Power @ rpm, hp	230 @ 6500 6	6	300 @ 5800 ⁷	7		360 @ 6300
Torque @ rpm, lb-ft.	200 @ 2750 6	3	300 @ 1400-	5000 ⁷		360 @ 3400
Engine-management system	MSV80 with I (2 sensors); V variable valve engine coolin functions incl strategy ⁶	/alvetronic, e timing,	MSD80 with F (2 sensors); c injection, varia timing, engine other function control strates	direct fuel able valve e cooling & as included in		ME9 with knock control, Valvetronic variable valve timing, engine cooling & other functions included in control strategy

⁷ – Specification applies to 535i/xi models.

 $[\]overline{}^{5}$ – VANOS = **V** Ariable **NO**ckenwellen Steuerung = variable camshaft control, or variable valve timing.

⁶ – Specification applies to 528i/xi models.

Engine & e lectrical (cont.)	528i Sedan	528xi Sedan	535i Sedan	535xi Sedan	535xi Sports Wagon	550i Sedan
Induction system	Single-stage ⁸					2-stage
Fuel requirement	Premium unle	eaded ²				
Fuel capacity, U.S. gal.	18.5 ²					
Battery capacity, amp-hr.	110 ²					
Alternator output rating, amp./W	180/2520 ²					

528i Sedan	528xi Sedan	535i Sedan	535xi Sedan	535xi Sports Wagon	550i Sedan
Front engine/ rear-wheel drive	Front engine/ all-wheel drive	Front engine/ rear-wheel drive	Front engine/ all-wheel drive	Front engine/ all-wheel drive	Front engine/ rear-wheel drive
Getrag I, 6-speed	ZF H, 6-speed	TBD	TBD	TBD	ZF G, 6-speed
4.32:1	4.35:1				4.06:1
2.46:1	2.50:1				2.40:1
1.66:1	1.66:1				1.58:1
1.23:1	1.23:1				1.19:1
1.00:1	1.00:1				1.00:1
0.85:1	0.85:1				0.87:1
3.94:1	3.93:1				3.68:1
3.38:1	3.46:1				2.93:1
	Sedan Front engine/ rear-wheel drive Getrag I, 6-speed 4.32:1 2.46:1 1.66:1 1.23:1 1.00:1 0.85:1 3.94:1	Sedan Sedan Front engine/ rear-wheel drive Front engine/ all-wheel drive Getrag I, 6-speed ZF H, 6-speed 4.32:1 4.35:1 2.46:1 2.50:1 1.66:1 1.66:1 1.23:1 1.23:1 1.00:1 0.85:1 3.94:1 3.93:1	SedanSedanSedanFront engine/ rear-wheel driveFront engine/ all-wheel driveFront engine/ rear-wheel driveGetrag I, 6-speedZF H, 6-speedTBD4.32:14.35:12.46:12.50:11.66:11.66:11.23:11.23:11.00:10.85:10.85:13.94:1	SedanSedanSedanSedanFront engine/ rear-wheel driveFront engine/ all-wheel driveFront engine/ all-wheel driveFront engine/ all-wheel driveFront engine/ all-wheel driveGetrag I, 6-speedZF H, 6-speedTBDTBD4.32:14.35:1TBDTBD2.46:12.50:1Front engine/ 6-speedFront engine/ all-wheel drive1.66:11.66:1Front engine/ 6-speedFront engine/ speed1.00:10.85:10.85:1Front engine/ speed3.94:13.93:1Front engine/ speedFront engine/ speed	SedanSedanSedanSedanSports WagonFront engine/ rear-wheel driveFront engine/ all-wheel driveFront engine/ all-wheel

⁸ – Specification applies to all 6-cylinder models.

Drivetrain (cont.)	528i Sedan	528xi Sedan	535i Sedan	535xi Sedan	535xi Sports Wagon	550i Sedan			
Automatic transmission	ZF 6 HP 19 TU ² , 6-speed STEPTRONIC with Adaptive Transmission Control, selectable Manual & Sport modes								
Ratios:									
1st	4.17:1 ²								
2nd	2.34:1 ²								
3rd	1.52:1 ²								
4th	1.14:1 ²								
5th	0.87:1 ²								
6th	0.69:1 ²								
Reverse	3.40:1 ²								
Final drive ratio	3.73:1	3.91:1	3:46:1	3.46:1	3.48:1	3.38:1			
Chassis	528i Sedan	528xi Sedan	535i Sedan	535xi Sedan	535xi Sports Wagon	550i Sedan			
Body/frame construction	Unitized; alu	minum front en	d, otherwise st	eel					
Front suspension	Struts, double-pivot lower arms, coil springs, twin-tube gas-pressure shock absorbers, anti-roll bar, subframe ² (528i/535i/550i: aluminum lower arms, steering knuckles, strut tubes, subframe & thrust plate) (528i/535i/550i ZSP: sport suspension calibration, Active Roll Stabilization)								
Rear suspension	absorbers, a	nti-roll bar; alui	ion; coil springs minum suspens suspension cali	sion system & s	subframe ²				

Chassis (cont.)	528i Sedan	528xi Sedan	535i Sedan	535xi Sedan	535xi Sports Wagon	550i Sedan		
Steering type:								
standard	Rack & pinion, Servotronic vehicle-speed-sensitive power assist ²							
optional	Rack & pinion, Active Steering; Servotronic vehicle-speed-sensitive power assist ²							
Overall ratio, standard steering Mechanically variable; mean ratio is 13.7:1 ²								
Overall ratio, optional Active Steering	Electrically/el	ectronically va	riable over wide	e range of 10.8	:1 – 18.0:1			
Turning circle, ft.	37.5	39.0	37.5	39.0	39.0	37.5		
4-wheel ventilated disc brakes wit aluminum calipers:	th							
Diameter x thickness, mm/in.								
Front	324 x 30/12.8	8 x 1.18	348 x 30/13.7	7 x 1.18		348 x 30/13.7 x 1.18		
Rear	320 x 20/12.6	6 x 0.79 ⁸	345 x 24/13.6 x 0.94			345 x 24/13.6 x 0.94		
Wheels:								
standard	Cast alloy, 17	′ x 7.5 ⁸				Cast alloy, 17 x 8.0		
optional (ZSP or stand-alone)	Cast alloy, 18 x 8.0 ^₅		Cast alloy, 18 x 8.0 F/18	x 9.0 R	Cast alloy, 18 x 8.0	Cast alloy, 19 x 8.5 F/19 x 9.5 R		
Tires:								
standard	225/50R-17 a	all-season ²						
optional (ZSP or stand-alone)	245/40R-18 run-flat perfoi	mance ^{6, 9}	245/40R-18 F 275/35-18 R run-flat perfor		245/40R-18 run-flat performance	245/35R-19 F/ 275/30-19 R ⁹ performance ⁹		

⁹ – Due to low-profile tires, please note: Wheels, tires and suspension parts are more susceptible to road hazard and consequential damages. Some models are not equipped with a spare tire and wheel. Performance tires are not recommended for driving in snow and ice conditions.

Chassis (cont.)	528i Sedan	528xi Sedan	535i Sedan	535xi Sedan	535xi Sports Wagon	550i Sedan		
Stability-enhancement system ²	Dynamic Stability Control (DSC), including Dynamic Traction Control, electronic brake proportioning, antilock braking (ABS), Dynamic Brake Control & cornering/braking stability enhancement (528xi/535xi models: add Hill Descent Control)							
Performance data	528i Sedan	528xi Sedan	535i Sedan	535xi Sedan	535xi Sports Wagon	550i Sedan		
Acceleration, 0-60 mph, sec. ¹⁰ :								
Manual transmission	6.5	7.1	TBD	TBD	TBD	5.4		
Automatic transmission	7.1	7.6	5.7	5.6	5.8	5.5		
Top speed, mph ¹¹ :	150	150	150	150	150	150		
Fuel economy, EPA est. MPG, ¹² city/highway:								
Manual transmission	17/27	17/25	TBD	TBD	TBD	15/22		
Automatic transmission	18/27	17/25	17/26	17/25	16/24	15/23		

ZSP – Sport Package NA – Not available or not applicable TBD – To Be Determined

#

¹⁰ – BMW AG test results. Actual acceleration results may vary depending on specification of vehicle; road and environmental conditions; testing procedures and driving style. These results should be used for comparison only, and verification should not be attempted on public roads. BMW urges you to obey all posted speed limits and to please wear your safety belt at all times.

¹¹ – Electronically limited

¹² – Preliminary EPA figures