

Technical Data - Europe.

BMW 3 Series Coupé (E92) - ACEA.

	320i Coupé	320i Coupé	325i Coupé	325i Coupé	330i Coupé	330i Coupé	335i Coupé	335i Coupé
Engine platform	N43B2000	N43B2000	N52B2501	N52B2501	N52B3001	N52B3001	N54B3000	N54B3000
Transmission	M6	A6	M6	A6	M6	A6	M6	A6
No of doors / seats	-	2 / 4	2 / 4	2 / 4	2 / 4	2 / 4	2 / 4	2 / 4
Vehicle length / width / height -unloaded-	mm	4580 / 1782 / 1395	4580 / 1782 / 1395	4580 / 1782 / 1395	4580 / 1782 / 1395	4580 / 1782 / 1395	4580 / 1782 / 1375	4580 / 1782 / 1375
Weelbase / Turning circle	mm / m	2760 / 11	2760 / 11	2760 / 11	2760 / 11	2760 / 11	2760 / 11	2760 / 11
Track front / rear	mm	1500 / 1513	1500 / 1513	1500 / 1513	1500 / 1513	1500 / 1513	1500 / 1507	1500 / 1507
Overhang rear	mm	1049	1049	1049	1049	1049	1049	1049
Ground clearance -empty-	mm	143	143	143	143	143	-	-
Shoulder width front / rear	mm	1404 / 1318	1404 / 1318	1404 / 1318	1404 / 1318	1404 / 1318	1404 / 1318	1404 / 1318
Elbow width front / rear	mm	1459 / 1403	1459 / 1403	1459 / 1403	1459 / 1403	1459 / 1403	1459 / 1403	1459 / 1403
Eff. head room front / rear	mm	975 / 934	975 / 934	975 / 934	975 / 934	975 / 934	975 / 934	975 / 934
Luggage capacity	m³	0,440	0,440	0,440	0,440	0,440	0,430	0,430
Fuel tank capacity	ltr	63	63	63	63	63	63	63
Curb weight -acc DIN-	kg	1360 / 1435	1390 / 1465	1420 / 1495	1450 / 1525	1470 / 1545	1485 / 1560	1525 / 1600
Axle load ratio -unloaded DIN-	%	49,0	48,3	49,1	48,4	48,4	47,9	48,3
Gross vehicle weight / Payload	kg	1810 / 450	1840 / 450	1900 / 480	1930 / 480	1950 / 480	1965 / 480	2005 / 480
Axle load limit front / rear	kg	880 / 995	880 / 995	905 / 1045	905 / 1045	930 / 1060	930 / 1060	960 / 1080
Trailer load braked -12% / 8%-	kg	1400 / 1600	1500 / 1600	1600 / 1700	1600 / 1700	1700 / 1800	1700 / 1800	1700 / 1800
Trailer load unbraked / roof load	kg	695 / 75	695 / 75	745 / 75	745 / 75	750 / 75	750 / 75	750 / 75
Engine type / cylinder / valves p cyl	-	In line / 4 / 4	In line / 4 / 4	In line / 6 / 4	In line / 6 / 4	In line / 6 / 4	In line / 6 / 4	In line / 6 / 4
Fuel management	-	MSD 80	MSD 80	MSV80	MSV80	MSV80	MSD80	MSD80
Effective displacement	cm³	1995	1995	2497	2497	2996	2979	2979
Stroke / Bore	mm	90 / 84	90 / 84	78,8 / 82	78,8 / 82	88 / 85	88 / 85	89,6 / 84
Nom power output / Engine speed	kW(hp) / 1/min	125 (170) / 6700	125 (170) / 6700	160 (218) / 6500	160 (218) / 6500	200 (272) / 6650	200 (272) / 6650	225 (306) / 5800
Max torque / Engine speed	Nm / 1/min	210 / 4250	210 / 4250	250 / 2750	250 / 2750	315 / 2750	315 / 2750	400 / 1300
RPM at max torque -range-	1/min	see 'Tor./Engine speed'	see 'Tor./Engine speed'	2750-4000	2750-4000	see 'Tor./Engine speed'	see 'Tor./Engine speed'	1300-5000
Compression ratio / Fuel type	-	12 / ROZ91-98	12 / ROZ91-98	11 / ROZ91-98	11 / ROZ91-98	10,7 / ROZ91-98	10,7 / ROZ91-98	10,2 / ROZ95-98
Exhaust emissions classification	-	EU4	EU4	EU4	EU4	EU4	EU4	EU4
Codification of reference gearbox	-	GETRAG I	ZF 6HP19	GETRAG I	ZF 6HP19 TÜ	ZF H	GM G66	ZF G
Gear ratio 1st/2nd/3rd	-	4,323 / 2,456 / 1,659	4,171 / 2,34 / 1,521	4,323 / 2,456 / 1,659	4,171 / 2,34 / 1,521	4,35 / 2,496 / 1,665	4,065 / 2,371 / 1,551	4,055 / 2,396 / 1,582
Gear ratio 4th/5th/6th/7th	-	1,23 / 1 / 0,848 / -	1,143 / 0,867 / 0,691 / -	1,23 / 1 / 0,848 / -	1,143 / 0,867 / 0,691 / -	1,23 / 1 / 0,851 / -	1,2 / 0,853 / 0,674 / -	1,192 / 1 / 0,872 / -
Reverse ratio	-	3,938	3,403	3,938	3,403	3,926	3,203	3,403
Final drive ratio	-	3,64	3,91	3,23	3,73	3,15	3,64	3,08
Steering type / ratio	-	Rack-and-pinion / 16	Rack-and-pinion / 16	Rack-and-pinion / 16	Rack-and-pinion / 16	Rack-and-pinion / 16	Rack-and-pinion / 16	Rack-and-pinion / 16
Brake front / diameter	-/mm	Ventilated Disc / 300	Ventilated Disc / 300	Ventilated Disc / 330	Ventilated Disc / 330	Ventilated Disc / 330	Ventilated Disc / 330	Ventilated Disc / 348
Brake rear / diameter	-/mm	Ventilated Disc / 300	Ventilated Disc / 300	Ventilated Disc / 300	Ventilated Disc / 300	Ventilated Disc / 336	Ventilated Disc / 336	Ventilated Disc / 336
Drag Cd / A / Cd x A	- / m² / m²	0,27 / 2,08 / 0,56	0,27 / 2,08 / 0,56	0,28 / 2,08 / 0,58	0,28 / 2,08 / 0,58	0,29 / 2,08 / 0,6	0,29 / 2,08 / 0,6	0,3 / 2,08 / 0,62
Top speed	km/h	230	228	247	245	250	250	250
Acceleration 0-100 Km/h	s	8,1	8,8	6,9	7,6	6,1	6,4	5,5
Acceleration 0-1000 m	s	28,8	29,3	27,3	28,0	26,0	26,0	24,5
Accel 80-120 Km/h 4/5 Gear	s	8,1 / 10,4 / -	- / - / -	7,4 / 9,4 / -	- / - / -	6,5 / 8,1 / -	- / - / -	5,2 / 6,2 / -
Weight ratio	kg/kW	10,9	11,1	8,9	9,1	7,4	7,4	6,8
Output per litre	kW/ltr	62,7	62,7	64,1	64,1	66,8	66,8	75,5
Fuel consumption -EU urban-	ltr/100km	8,7	8,8	12,1	12,9	12,8	12,9	14,3
Fuel consumption -EU extra-urban-	ltr/100km	4,9	5,0	6,2	6,7	6,5	6,8	7,0
Fuel consumption -EU01 / Range	ltr/100km / km	6,3 / 1000	6,4 / 980	8,4 / 750	9 / 700	8,8 / 715	9 / 700	9,5 / 665
CO2-emission -EU-	g/km	151	154	203	218	212	218	228
Tyre type -front-	-	225/45 R17 91V RSC	225/45 R17 91V RSC	245/45 R17 91W RSC	245/45 R17 91W RSC	225/45 R17 91W RSC	225/45 R17 91W RSC	225/45 R17 91W RSC
Tyre type -rear-	-	225/45 R17 91V RSC	225/45 R17 91V RSC	245/45 R17 91W RSC	245/45 R17 91W RSC	225/45 R17 91W RSC	225/45 R17 91W RSC	255/40 R17 94W RSC
Front rim	-	8J x 17 Light alloy	8J x 17 Light alloy	8J x 17 Light alloy	8J x 17 Light alloy	8J x 17 Light alloy	8J x 17 Light alloy	8J x 17 Light alloy
Rear rim	-	8J x 17 Light alloy	8J x 17 Light alloy	8J x 17 Light alloy	8J x 17 Light alloy	8J x 17 Light alloy	8J x 17 Light alloy	8,5J x 17 Light alloy
Wheel offset -front/rear-	mm	34 / 34	34 / 34	34 / 34	34 / 34	34 / 34	34 / 34	34 / 37
Radiator incl. heater / Engine oil exchange quantity	ltr	- / -	- / -	8,2 / 6,5	8,5 / 6,5	8,2 / 6,5	8,5 / 6,5	8,2 / 6,5
Transmission fluid -exchange quantity-	ltr	Permanent filling	Permanent filling	Permanent filling	Permanent filling	Permanent filling	Permanent filling	Permanent filling
Battery capacity / installed position	Ah/-	70 / Luggage comp.	70 / Luggage comp.	70 / Luggage comp.	70 / Luggage comp.	70 / Luggage comp.	70 / Luggage comp.	70 / Luggage comp.
Alternator output rating	A/W	110 / 1540	110 / 1540	155 / 2170	180 / 2520	155 / 2170	180 / 2520	180 / 2520

Technical Data - Europe.

BMW 3 Series Coupé (E92) - ACEA.

	320d Coupé	320d Coupé	325d Coupé	325d Coupé	330d Coupé	330d Coupé	335d Coupé	
Engine platform	N47D20O0	N47D20O0	M57D30U2	M57D30U2	M57D30O2	M57D30O2	M57D30T2	
Transmission	M6	A6	M6	A6	M6	A6	A6	
No of doors / seats	-	2 / 4	2 / 4	2 / 4	2 / 4	2 / 4	2 / 4	
Vehicle length / width / height -unloaded-	mm	4580 / 1782 / 1395	4580 / 1782 / 1395	4580 / 1782 / 1395	4580 / 1782 / 1395	4580 / 1782 / 1395	4580 / 1782 / 1375	
Weelbase / Turning circle	mm / m	2760 / 11	2760 / 11	2760 / 11	2760 / 11	2760 / 11	2760 / 11	
Track front / rear	mm	1500 / 1513	1500 / 1513	1500 / 1513	1500 / 1513	1500 / 1513	1500 / 1507	
Overhang rear	mm	1049	1049	1049	1049	1049	1049	
Ground clearance -empty-	mm	143	143	143	143	143	-	
Shoulder width front / rear	mm	1404 / 1318	1404 / 1318	1404 / 1318	1404 / 1318	1404 / 1318	1404 / 1318	
Elbow width front / rear	mm	1459 / 1403	1459 / 1403	1459 / 1403	1459 / 1403	1459 / 1403	1459 / 1403	
Eff. head room front / rear	mm	975 / 934	975 / 934	975 / 934	975 / 934	975 / 934	975 / 934	
Luggage capacity	m³	0,440	0,440	0,440	0,440	0,440	0,430	
Fuel tank capacity	ltr	61	61	61	61	61	61	
Curb weight -acc DIN-	kg	1420 / 1495	1430 / 1505	1515 / 1590	1525 / 1600	1525 / 1600	1540 / 1615	1570 / 1645
Axle load ratio -unloaded DIN-	%	48,7	48,4	48,0	47,7	47,7	47,2	47,3
Gross vehicle weight / Payload	kg	1900 / 480	1910 / 480	1995 / 480	2005 / 480	2005 / 480	2020 / 480	2050 / 480
Axle load limit front / rear	kg	900 / 1035	900 / 1035	960 / 1070	960 / 1070	970 / 1075	970 / 1075	990 / 1085
Trailer load braked -12% / 8%-	kg	1600 / 1800	1600 / 1800	1800 / 1800	1800 / 1800	1800 / 1800	1800 / 1800	1800 / 1800
Trailer load unbraked / roof load	kg	745 / 75	745 / 75	750 / 75	750 / 75	750 / 75	750 / 75	750 / 75
Engine type / cylinder / valves p cyl	-	In line / 4 / 4	In line / 4 / 4	In line / 6 / 4	In line / 6 / 4	In line / 6 / 4	In line / 6 / 4	In line / 6 / 4
Fuel management	-	DDE71	DDE71	CR-System DDE6	CR-System DDE6	DDE6	DDE6	DDE6
Effective displacement	cm³	1995	1995	2993	2993	2993	2993	2993
Stroke / Bore	mm	90 / 84	90 / 84	90 / 84	90 / 84	90 / 84	90 / 84	90 / 84
Nom power output / Engine speed	kW(hp) / 1/min	130 (177) / 4000	130 (177) / 4000	145 (197) / 3750	145 (197) / 3750	170 (231) / 4000	170 (231) / 4000	210 (286) / 4400
Max torque / Engine speed	Nm / 1/min	350 / 2000	350 / 2000	400 / 1300	400 / 1300	500 / 1750	500 / 1750	580 / 1750
RPM at max torque -range-	1/min	see 'Tor./Engine speed'	see 'Tor./Engine speed'	1300-3250	1300-3250	1750-3000	1750-3000	1750-2250
Compression ratio / Fuel type	-	16 / Diesel	16 / Diesel	17 / Diesel	17 / Diesel	17 / Diesel	17 / Diesel	17 / Diesel
Exhaust emissions classification	-	EU4	EU4	EU4	EU4	EU4	EU4	EU4
Codification of reference gearbox	-	ZF Hweit	ZF 6HP19 TÜ	ZF Gweit	ZF 6HP26 TÜ	ZF Gweit	ZF 6HP26 TÜ	ZF 6HP26 TÜ
Gear ratio 1st/2nd/3rd	-	5,14 / 2,83 / 1,804	4,171 / 2,34 / 1,521	5,08 / 2,804 / 1,783	4,171 / 2,34 / 1,521	5,08 / 2,804 / 1,783	4,171 / 2,34 / 1,521	4,171 / 2,34 / 1,521
Gear ratio 4th/5th/6th/7th	-	1,257 / 1 / 0,831 / -	1,143 / 0,867 / 0,691 / -	1,26 / 1 / 0,835 / -	1,143 / 0,867 / 0,691 / -	1,26 / 1 / 0,835 / -	1,143 / 0,867 / 0,691 / -	1,143 / 0,867 / 0,691 / -
Reverse ratio	-	4,638	3,403	4,607	3,403	4,607	3,403	3,403
Final drive ratio	-	2,56	3,15	2,35	2,79	2,35	2,81	2,81
Steering type / ratio	-	Rack-and-pinion / 16	Rack-and-pinion / 16	Rack-and-pinion / 16	Rack-and-pinion / 16	Rack-and-pinion / 16	Rack-and-pinion / 16	Rack-and-pinion / 16
Brake front / diameter	-/mm	Ventilated Disc / 312	Ventilated Disc / 312	Ventilated Disc / 330	Ventilated Disc / 330	Ventilated Disc / 348	Ventilated Disc / 348	Ventilated Disc / 348
Brake rear / diameter	-/mm	Ventilated Disc / 300	Ventilated Disc / 300	Ventilated Disc / 336	Ventilated Disc / 336	Ventilated Disc / 336	Ventilated Disc / 336	Ventilated Disc / 336
Drag Cd / A / Cd x A	- / m² / m²	0,28 / 2,08 / 0,58	0,28 / 2,08 / 0,58	0,28 / 2,08 / 0,58	0,28 / 2,08 / 0,58	0,29 / 2,08 / 0,6	0,29 / 2,08 / 0,6	0,3 / 2,08 / 0,62
Top speed	km/h	232	230	238	236	250	250	250
Acceleration 0-100 Km/h	s	7,8	7,9	7,3	7,5	6,6	6,7	6,1
Acceleration 0-1000 m	s	28,4	28,5	27,8	27,7	26,5	27,1	25,3
Accel 80-120 Km/h 4/5 Gear	s	6,5 / 8,3 / -	- / - / -	6,3 / 8,1 / -	- / - / -	4,9 / 6,3 / -	- / - / -	- / - / -
Weight ratio	kg/kW	10,9	11,0	10,4	10,5	9,1	9,1	7,5
Output per litre	kW/ltr	65,2	65,2	48,4	48,4	56,8	56,8	70,2
Fuel consumption -EU urban-	ltr/100km	6,1	7,2	8,6	9,3	8,9	10,0	10,3
Fuel consumption -EU extra-urban-	ltr/100km	4,2	4,5	5,1	5,5	5,1	5,9	5,9
Fuel consumption -EU01 / Range	ltr/100km / km	4,9 / 1240	5,5 / 1105	6,4 / 950	6,9 / 880	6,5 / 940	7,4 / 825	7,5 / 815
CO2-emission -EU-	g/km	131	145	171	184	174	197	200
Tyre type -front-	-	225/45 R17 91V RSC	225/45 R17 91V RSC	225/45 R17 91W RSC	225/45 R17 91W RSC	225/45 R17 91W RSC	225/45 R17 91W RSC	225/45 R17 91W RSC
Tyre type -rear-	-	225/45 R17 91V RSC	225/45 R17 91V RSC	225/45 R17 91W RSC	225/45 R17 91W RSC	225/45 R17 91W RSC	225/45 R17 91W RSC	255/40 R17 94W RSC
Front rim	-	8J x 17 Light alloy	8J x 17 Light alloy	8J x 17 Light alloy	8J x 17 Light alloy	8J x 17 Light alloy	8J x 17 Light alloy	8J x 17 Light alloy
Rear rim	-	8J x 17 Light alloy	8J x 17 Light alloy	8J x 17 Light alloy	8J x 17 Light alloy	8J x 17 Light alloy	8J x 17 Light alloy	8,5J x 17 Light alloy
Wheel offset -front/rear-	mm	34 / 34	34 / 34	34 / 34	34 / 34	34 / 34	34 / 34	34 / 37
Radiator incl. heater / Engine oil exchange quantity	ltr	7,2 / 5,5	7,5 / 5,5	7,9 / 7,5	8,2 / 7,5	7,9 / 7,5	8,2 / 7,5	8,2 / 7,5
Transmission fluid -exchange quantity-	ltr	Permanent filling	Permanent filling	Permanent filling	Permanent filling	Permanent filling	Permanent filling	Permanent filling
Battery capacity / installed position	Ah/-	90 / Luggage comp.	90 / Luggage comp.	90 / Luggage comp.	90 / Luggage comp.	90 / Luggage comp.	90 / Luggage comp.	90 / Luggage comp.
Alternator output rating	A/W	180 / 2520	- / -	150 / 2100	150 / 2100	150 / 2100	150 / 2100	170 / 2380

Technical Data - Europe.

BMW 3 Series Coupé (E92) - ACEA.

	325xi Coupé	325xi Coupé	330xi Coupé	330xi Coupé	330xd Coupé	330xd Coupé	
Engine platform	N52B25O1	N52B25O1	N52B30O1	N52B30O1	M57D30O2	M57D30O2	
Transmission	M6	A6	M6	A6	M6	A6	
No of doors / seats	-	2 / 4	2 / 4	2 / 4	2 / 4	2 / 4	
Vehicle length / width / height -unloaded-	mm	4580 / 1782 / 1395	4580 / 1782 / 1395	4580 / 1782 / 1395	4580 / 1782 / 1395	4580 / 1782 / 1395	
Weelbase / Turning cicle	mm / m	2760 / 11,8	2760 / 11,8	2760 / 11,8	2760 / 11,8	2760 / 11,8	
Track front / rear	mm	1500 / 1513	1500 / 1513	1500 / 1513	1500 / 1513	1500 / 1513	
Overhang rear	mm	1049	1049	1049	1049	1049	
Ground clearance -empty-	mm	143	143	143	143	143	
Shoulder width front / rear	mm	1404 / 1318	1404 / 1318	1404 / 1318	1404 / 1318	1404 / 1318	
Elbow width front / rear	mm	1459 / 1403	1459 / 1403	1459 / 1403	1459 / 1403	1459 / 1403	
Eff. head room front / rear	mm	975 / 934	975 / 934	975 / 934	975 / 934	975 / 934	
Luggage capacity	m³	0,440	0,440	0,440	0,440	0,440	
Fuel tank capacity	ltr	63	63	63	61	61	
Curb weight -acc DIN-	kg	1530 / 1605	1550 / 1625	1570 / 1645	1585 / 1660	1625 / 1700	1640 / 1715
Axle load ratio -unloaded DIN-	%	46,2	45,9	46,3	45,9	45,4	45,2
Gross vehicle weight / Payload	kg	2010 / 480	2030 / 480	2050 / 480	2065 / 480	2105 / 480	2120 / 480
Axle load limit front / rear	kg	1000 / 1055	1000 / 1055	1015 / 1075	1015 / 1075	1035 / 1090	1035 / 1090
Trailer load braked -12% / 8%-	kg	1700 / 1800	1700 / 1800	1800 / 1800	1800 / 1800	1800 / 1800	1800 / 1800
Trailer load unbraked / roof load	kg	750 / 75	750 / 75	750 / 75	750 / 75	750 / 75	750 / 75
Engine type / cylinder / valves p cyl	-	In line / 6 / 4	In line / 6 / 4	In line / 6 / 4	In line / 6 / 4	In line / 6 / 4	In line / 6 / 4
Fuel management	-	MSV80	MSV80	MSV80	MSV80	DDE6	DDE6
Effective displacement	cm³	2497	2497	2996	2996	2993	2993
Stroke / Bore	mm	78,8 / 82	78,8 / 82	88 / 85	88 / 85	90 / 84	90 / 84
Nom power output / Engine speed	kW(hp) / 1/min	160 (218) / 6500	160 (218) / 6500	200 (272) / 6650	200 (272) / 6650	170 (231) / 4000	170 (231) / 4000
Max torque / Engine speed	Nm / 1/min	250 / 2750	250 / 2750	315 / 2750	315 / 2750	500 / 1750	500 / 1750
RPM at max torque -range-	1/min	2750-4000	2750-4000	see 'Tor./Engine speed'	see 'Tor./Engine speed'	1750-3000	1750-3000
Compression ratio / Fuel type	-	11 / ROZ91-98	11 / ROZ91-98	10,7 / ROZ91-98	10,7 / ROZ91-98	17 / Diesel	17 / Diesel
Exhaust emissions classification	-	EU4	EU4	EU4	EU4	EU4	EU4
Codification of reference gearbox	-	ZF H	GM GM6	ZF H	GM GM6	ZF Gweit	ZF 6HP26 Tü
Gear ratio 1st/2nd/3rd	-	4,35 / 2,496 / 1,665	4,065 / 2,371 / 1,551	4,35 / 2,496 / 1,665	4,065 / 2,371 / 1,551	5,08 / 2,804 / 1,783	4,171 / 2,34 / 1,521
Gear ratio 4th/5th/6th/7th	-	1,23 / 1 / 0,851 / -	1,2 / 0,853 / 0,674 / -	1,23 / 1 / 0,851 / -	1,2 / 0,853 / 0,674 / -	1,26 / 1 / 0,835 / -	1,143 / 0,867 / 0,691 / -
Reverse ratio	-	3,926	3,200	3,926	3,200	4,607	3,403
Final drive ratio	-	3,23	3,91	3,15	3,64	2,47	2,93
Steering type / ratio	-	Rack-and-pinion / 18,2	Rack-and-pinion / 18,2	Rack-and-pinion / 18,2	Rack-and-pinion / 18,2	Rack-and-pinion / 18,2	Rack-and-pinion / 18,2
Brake front / diameter	-/mm	Ventilated Disc / 330	Ventilated Disc / 330	Ventilated Disc / 330	Ventilated Disc / 330	Ventilated Disc / 348	Ventilated Disc / 348
Brake rear / diameter	-/mm	Ventilated Disc / 300	Ventilated Disc / 300	Ventilated Disc / 336	Ventilated Disc / 336	Ventilated Disc / 336	Ventilated Disc / 336
Drag Cd / A / Cd x A	- / m² / m²	0,3 / 2,08 / 0,62	0,3 / 2,08 / 0,62	0,3 / 2,08 / 0,62	0,3 / 2,08 / 0,62	0,3 / 2,08 / 0,62	0,3 / 2,08 / 0,62
Top speed	km/h	244	238	250	250	242	240
Acceleration 0-100 Km/h	s	7,4	8,0	6,2	6,7	6,5	6,6
Acceleration 0-1000 m	s	28,3	28,4	26,7	26,7	26,8	26,9
Accel 80-120 Km/h 4/5 Gear	s	8,5 / 10,7 / -	- / - / -	7 / 9 / -	- / - / -	5,2 / 6,6 / -	- / - / -
Weight ratio	kg/kW	9,6	9,7	7,8	7,9	9,6	9,6
Output per litre	kW/ltr	64,1	64,1	66,8	66,8	56,8	56,8
Fuel consumption -EU urban-	ltr/100km	13,0	14,4	13,9	14,6	9,6	10,8
Fuel consumption -EU extra-urban-	ltr/100km	7,0	7,3	7,1	7,5	5,8	6,4
Fuel consumption -EU01 / Range	ltr/100km / km	9,2 / 685	9,9 / 635	9,6 / 655	10,1 / 625	7,2 / 845	8 / 765
CO2-emission -EU-	g/km	221	238	230	243	192	213
Tyre type -front-	-	225/45 R17 91W RSC	225/45 R17 91W RSC	225/45 R17 91W RSC	225/45 R17 91W RSC	225/45 R17 91W RSC	225/45 R17 91W RSC
Tyre type -rear-	-	225/45 R17 91W RSC	225/45 R17 91W RSC	225/45 R17 91W RSC	225/45 R17 91W RSC	225/45 R17 91W RSC	225/45 R17 91W RSC
Front rim	-	8J x 17 Light alloy	8J x 17 Light alloy	8J x 17 Light alloy	8J x 17 Light alloy	8J x 17 Light alloy	8J x 17 Light alloy
Rear rim	-	8J x 17 Light alloy	8J x 17 Light alloy	8J x 17 Light alloy	8J x 17 Light alloy	8J x 17 Light alloy	8J x 17 Light alloy
Wheel offset -front/rear-	mm	34 / 34	34 / 34	34 / 34	34 / 34	34 / 34	34 / 34
Radiator incl. heater / Engine oil exchange quantity	ltr	8,2 / 6,5	8,5 / 6,5	8,2 / 6,5	8,5 / 6,5	7,9 / 7,5	8,2 / 7,5
Transmission fluid -exchange quantity-	ltr	Permanent filling	Permanent filling	Permanent filling	Permanent filling	Permanent filling	Permanent filling
Battery capacity / installed position	Ah/-	70 / Luggage comp.	70 / Luggage comp.	70 / Luggage comp.	70 / Luggage comp.	90 / Luggage comp.	90 / Luggage comp.
Alternator output rating	A/W	180 / 2520	180 / 2520	180 / 2520	180 / 2520	150 / 2100	150 / 2100